

U-Link

16CH 8MP NVR, 4SATA Interface

UL-16NVR4K48-IP



FEATURES

Support Ultra265/H.265/H.264 video formats.

16-channel input.

Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T.

HDMI and VGA simultaneous output.

Up to 8 Megapixels resolution recording.

U-Link

16CH 8MP NVR, 4SATA Interface

UL-16NVR4K48-IP



FEATURES

Accurate retrieval, instant playback.

4 SATA HDDs, Up to 10TB for each HDD.

AR technology to enhance the storage reliability when the network is disconnected.

Support cloud upgrade.



SPECIFICATION	
Model	UL-16NVR4K48-IP
Video/Audio Input	
IP Video Input	16-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	160Mbps
Outgoing Bandwidth	64 Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPOE
Video/Audio Output	
HDMI/VGA Output	HDMI: 4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60
Audio Output	1-ch. RCA
Recording Resolution	8MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/CIF
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16
Decoding	
Decoding format	Ultra 265. H.265. H.264
Live view/Playback	8MP/5MP/4MP/3MP/1080p/960p/960H/720p/D1/2CIF/CIF
Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
Hard Disk	
SATA	4 SATA interfaces
Capability	up to 10TB for each HDD
External Interface	
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
General	
Power Supply	12V DC Power Consumption: ≤ 15W(without HDD)
Working Environment	-10°C~+55°C (+14°F~+131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions (WxDxH)	440mm x344mm x50mm (17.3" x13.5" x2.0")
Weight (without HDD)	≤ 3.15 Kg (6.94 lb)