

U-Link

2MP Outdoor Bullet IP Camera - IR 25m

UL-2BIR25F-IP



FEATURES

1/2.9" Full HD
CMOS Sensor

H.264/H.264+/H.265/H.265+/JPEG
/AVI/MJPEG Compression Method

Fixed Lens 3.6 mm

Infrared Distance
25m Max.

IP 67 Outdoor
Metal case.



2MP Outdoor Bullet IP Camera - IR 25m

UL-2BIR25F-IP



SPECIFICATION

Camera

Image Sensor	1/2.9" Full HD CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimun Illumination	0.01Lux
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
AGC	Support
Auto Iris	Support

Lens

Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP

Night Vision

Infrared LED	14μ x 20PCS
Infrared Distance	25M
IR Status	Auto Control
IR Power On	Manual & Timed mode

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP,UDP
ONVIF	Support ONVIF 2.4(Profile S/T/G)
P2P	YES
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2048*1536@20fps
Main Stream 2	1920*1080@30fps
Main Stream 3	1280*720@30fps



2MP Outdoor Bullet IP Camera - IR 25m

UL-2BIR25F-IP



Sub Stream 1	720*480@30fps
Sub Stream 2	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
BLC	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
Interface	
Audio	Optional
General	
Housing	Metal , IP67 out door camera
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 900mA
Dimension	158(W) x 76(H) x 73(D)mm
Weight	650g