

U-Link

2MP Outdoor VF Bullet IP Camera - IR 40m

UL-2BIR40V-IP



FEATURES

1/2.8" SONY Starvis Back-illuminated CMOS Sensor

H.265+/H.265/H.264+/H.264 Compression Method

2.8-12mm Varifocal Lens

IR Distance 40m Max.

IP 67 Outdoor Metal case.



2MP Outdoor VF Bullet IP Camera - IR 40m

UL-2BIR40V-IP



SPECIFICATION

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimun Illumination	0.002Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Auto/Manual iris	Yes
AGC	Support

Lens

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal
Pixels	2MP

Night Vision

Infrared LED	42μ x 4PCS
Infrared Distance	40m
IR Status	Auto Control
IR Power On	Auto Control

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4(Profile S/T)
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps



2MP Outdoor VF Bullet IP Camera - IR 40m

UL-2BIR40V-IP



Sub Stream 1	720*480@15fps 720*480@30fps
Tri Stream	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(-Flicker Control), Video Tampering, HLC
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	WDR: 96dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Interface	
Audio	Optional
SD Card Slot	SD Card Slot Optional, Support Max 512GB
General	
Housing	Metal , IP67
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 950mA
Dimension	211(W) x 92(H) x 90(D)mm
Weight	1400g