



2MP fixed lens indoor dome Camera, IR 20m

UL-2DIR20FP-IP



FEATURES

1/2.9" Full HD CMOS Sensor

Fixed lens 2.8 mm

Minimum Illumination 0.01Lux
at color mode

Infrared Distance 20m

DWDR



2MP fixed lens indoor dome Camera, IR 20m

UL-2DIR20FP-IP



Technical Specification

Camera

Image Sensor	1/2 9" Full HD CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1920(H)*1080(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimun Illumination	0.01Lux at color mode
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
AGC	Support

Lens

Focus Length	2.8 mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	2 MP

Night Vision

Infrared LED	14ux 18PCS
Infrared Distance	20M
I Status	Auto Control
IR Power On	Smart, Manual & Timed mode

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP,UDP
ONVIF	Support ONVIF 2.4(Profile S/T/G)
P2P	YES
POE	Support IEEE 802.3af
Main Stream 1	2304*1296@20fps
Main Stream 2	1920*1080@30fps
Main Stream 3	1280*720@30fps
Sub Stream 1	720*480@30fps
Sub Stream 2	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad



2MP fixed lens indoor dome Camera, IR 20m

UL-2DIR20FP-IP



Technical Specification

Camera Features

Day/Night	Color / B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK(Flicker Control)
Corridor Pattern	Support
Defog Mode	Support
BLC	Support
WDR	DWDR
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web

Interface

Audio	Yes
-------	-----

General

Housing	Plastic
Anti-cut Bracket	Optional Wall Bracket
IR Cut Filter	YES
Operation Temperature	-20°C~+60°C RH95% Max
Storage Temperature	-20°C ~+60°C RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	ø 99× 81(H) mm
Weight	300g