



2.0 Megapixel IP Camera
3.7mm pinhole lens
UL-2PH-IP



Technical Term

- HD: high definition, 2.0MP: 1920*1080@15fps
- P2P: PNP, plug-and-play, a progress of interface technique, plug and play, no need people operate.
- ONVIF (Version 2.0): Open Network Video Interface Forum, ONVIF is committed to the adoption of IP in the security market. The ONVIF specification will ensure interoperability between products regardless of manufacturer.
- POE, DC12V



2.0 Megapixel IP Camera
3.7mm pinhole lens
UL-2PH-IP



Introduction

This is a IP Camera who not only capture video like common CCTV Camera, but also compress data and send data to end-user via LAN, Internet or WLAN. You can publish and view video only need to plug network cable and power ip camera. IP Camera has its own microprocessor, often use linux operation system, built-in web server, support multiple network protocols. IP camera has its own ip address and DDNS domain name, it can be viewed by inputting ip address into IE browser address bar or CMS software.



2.0 Megapixel IP Camera
3.7mm pinhole lens
UL-2PH-IP



Character

- 1- High performance 2.0megapixel M330+F37 CMOS Image
- 2- Clear video Full HD 1080P
- 3- 1/25 seconds -1/10000 seconds shutter speed
- 4- System: Embedded Linux, Built-in Web Server, Remote Setup Enable
- 5- Compression: H.265 encoding, Pure Hardware Compression, 3D image noise reduction technology
- 6- Application Function: Motion detectionEmail Alarm, Image flip, etc.
- 7- Remote Function: Setup Menu, snapshots, supervisory control etc.
- 8- Remote View: IE browser,cloud service platform and smart phone apps.
- 9- Smart Phone: Support iphone, ipad, Android, remote monitoring via Apps
- 10- Protocol: TCP/IP,RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP



2.0 Megapixel IP Camera 3.7mm pinhole lens UL-2PH-IP



Tech. Parameter	
System	Embedded linux
Mount Types	Ceiling Bracket
Performance	Motion detection Email alarm , Night Vision , Dual-stream
Language	Chinese , English
Network Interface	RJ45 (Base-10/100MB)
Pixels	2.0MP
Resolution	2.0MP:1920*1080
Lens	3.7mm
Angle of view	Wall mount 180 degrees,Ceiling mount 360 degrees
IR	no
Video compression	H.264/MJPEG
Main Stream	1920.*1080; 1280 x 960
Sub Stream	1280 x 720, 960 x 540 , 640 x 360 , 480 x 270 , 352 x 288 , 320x 240
Web Browser	IE
Network Transmission	P2P
Network protocol	TCP/IP, HTTP, FTP, NTP, RTP, ARP, ICMP, DHCP, SMTP, POP3,DNS, RTCP
Environment	Indoor
Working temperature	-10~+ 50degree
Input voltage	DC12V



2.0 Megapixel IP Camera
3.7mm pinhole lens
UL-2PH-IP



Packing List

- 1pc ip camera
- 1set screws
- 1pc DC12V adaptor/poe

Application

The camera can be used in following both outdoor and indoor monitor environment: Street, Garden, School, Family, Shop, Office, Building, Chain enterprise, Large factory machine room, Remote elder children nurse, Public buildings, Nobody dangerous environment monitor, Financial institution branch monitor, Traffic monitor and etc.