

# U-Link

32CH, NVR, 4 SATA Interface

**UL-32NVR4K48-IP**



## FEATURES

Support Ultra265/H.265/H.264 video formats.

32-channel input.

Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T.

HDMI and VGA simultaneous output.

Up to 8 Megapixels resolution recording.

# U-Link

32CH, NVR, 4 SATA Interface

UL-32NVR4K48-IP



## FEATURES

Accurate retrieval, instant playback.

4 SATA HDDs, Up to 10TB for each HDD.

AR technology to enhance the storage reliability when the network is disconnected.

Support cloud upgrade.

# U-Link

32CH, NVR, 4 SATA Interface

UL-32NVR4K48-IP



| SPECIFICATION             |   |
|---------------------------|---|
| <b>Model</b>              | UL-32NVR4K48-IP   |
| <b>Video/Audio Input</b>  |   |
| IP Video Input            | 32-ch   |
| Two-way Audio Input       | 1-ch, RCA   |
| <b>Network</b>            |   |
| Incoming Bandwidth        | 160Mbps   |
| Outgoing Bandwidth        | 64 Mbps   |
| Remote Users              | 128   |
| Protocols                 | P2P, UPnP, NTP, DHCP, PPPOE   |
| <b>Video/Audio Output</b> |   |
| HDMI/VGA Output           | HDMI:<br>4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60<br>1024x768@60<br>VGA:<br>1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60 |
| Audio Output              | 1-ch. RCA   |
| Recording Resolution      | 8MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/CIF  |
| Synchronous Playback      | 32-ch   |
| Corridor Mode Screen      | 3/4/5/7/9/10/12/16/32   |
| <b>Decoding</b>           |   |
| Decoding format           | Ultra 265. H.265. H.264   |
| Live view/Playback        | 8MP/5MP/4MP/3MP/1080p/960p/960H/720p/D1/2CIF/CIF  |
| Capability                | 2 x4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x1080p@30, 16 x 720p@30, 32 x D1  |
| <b>Hard Disk</b>          |   |
| SATA                      | 4 SATA interfaces   |
| Capability                | up to 10TB for each HDD   |
| <b>External Interface</b> |   |
| Network Interface         | 2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces  |
| USB Interface             | Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0  |
| <b>General</b>            |   |
| Power Supply              | 12V DC<br>Power Consumption: ≤ 15W( without HDD)  |
| Working Environment       | -10°C~+55°C (+14°F~+131°F), Humidity ≤ 90% RH(non-condensing)   |
| Dimensions (WxDxH)        | 440mm x344mm x50mm (17.3" x13.5" x2.0")   |
| Weight (without HDD)      | ≤ 3.15 Kg (6.94 lb)   |