





## USLink 36CH H.265/H.264 /MJPEG NVR UL-36NVR4K-IP



SPECIFICATION	
Model NO.	UL-36NVR4K-IP
Video & Audio Input	
Video Input	36ch network compressed video input (compatible with 4K with 4K resolution)
Bandwidth	512M
Audio Input	IPC composite stream network audio input
Video & Audio Output	
HDMI Output	1CH HDMI, 1ch VGA,Resolution:3840×2160/30Hz, 1920×1080/60Hz, 1280X1024/60Hz
Audio Output	1CH RCA
Video & Audio Encording	
Video Format	H.265/H.264 /MJPEG
Video Resolution	8M/5M/3M/1080P/720P
Decode Playback	Support Max 16CH 1080P playback,4CH 4K Playback
Video Management	
Video/Capture Mode	Manual recording, video recording, event recording, moving detection, video recording, alarm recording, dynamic test or alarm recording, dynamic test and alarm recording
Playback Mode	Instant playback, regular playback, event playback, external file playback, log playback
Backup Mode	Regular backup, event backup, video clip backup
HDD	
Туре	9x SATA+1x eSATA
Maximum Capacity	Each port supports MAX 8TB HDD
External Ports	
Network	2*RJ45 10M/100M/1000M self-adaptive LAN port
USB	2x USB2.0 front port, 1x USB3.0 rear port
Serial Port	RS-485
Alarm Input	4ch alarm input, low level active, green terminal port
Alarm Output	4ch alarm output, relay contact (1A@24VDC), NO、NC programmable
Network Management	
Network Protocol	ONVIF (support version 2.4), IPv4, UPnP (plug and play), NTP (network school time), SADP (automatic search IP address), PPPoE (dial-up Internet), DHCP (automatic access to IP addresses), etc.
General	(automate decess to 11 days essent) etai
Power Supply	110-220V~ 50/60Hz 200W
Working Temperature	-10°C+55°C
Working Humidity	10%-90%
Power Consumption	≤30W
Dimension	Equipment : 440mm×430mm×90mm Packing :539mmX530mmX225mm
Weight(without HDD)	N.W: 7.4kg (without HDD) with package:9.8kg
Installation Method	Desktop installation
Rear panel	

