

U-Link

5MP indoor Dome Camera -IR 30m

UL-5DIR30V-AHD



FEATURES

1/2.5" CMOS Sensor

AHD/CVI/TVI/CVBS
4 IN 1

2.8-12mm Varifocal
Lens

IR Distance Max.
30m

IP66 Outdoor,
OSD&UTC Support



5MP indoor Dome Camera -IR 30m

UL-5DIR30V-AHD



SPECIFICATION

Camera

Image Sensor	1/2.5" CMOS sensor
Image Resolution	5M:2592*1944 4M:2560*1440 2M:1920*1080
Electronic Shutter	Auto
TV System	PAL/NTSC
Video Output Mode	AHD/TVI: 5M@20fps/12.5fps, 4M@30fps/15fps, 2M@30fps/25fps; CVI: 4M@30fps/25fps, 2M@30fps/25fps
Scanning System	Progressive Scan

Lens

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal

Night Vision

IR Cut Filter	YES
Infrared LED	42 x 4PCS
Infrared Distance	30m
IR Status	AGC Auto Control



5MP indoor Dome Camera -IR 30m

UL-5DIR30V-AHD



Camera Features

Day/Night	YES
OSD Menu	YES
WDR	DWDR
UTC	YES
Noise Reduction	DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO

General

Housing	Metal, IP67
Bracket	NO
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 750mA
Dimension	Ø142 x 142(H) mm
Weight	1.2Kgs