

U-Link

8 MP IP Bullet camera , Fixed Lens

UL-8BIR20F-IP



FEATURES

Value IP Bullet

1/2.7" SmartSens CMOS sensor

H.265+/H.265/H.264+/H.264 Compression Method

3.6mm Fixed Lens

IR Distance 20m Max

With Internal POE and SD Card Slot

U-Link

8 MP IP Bullet camera , Fixed Lens

UL-8BIR20F-IP



SPECIFICATION

Camera

Image Sensor	1/2.7" Smartens CMOS sensor
Resolution	8MP
Effective Pixels	3872(H)*2180(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimun Illumination	0.01Lux
S/N Ratio	>52dB
Scanning System	Progressive
Video Output	Network
Reset button	Optional
White balance	Auto/manual
Manual/auto iris	Yes

Lens

Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	8MP

Night Vision

Infrared LED	42μ x 2PCS
Infrared Distance	20m
IR Status	Auto Control
IR Power On	Manual & Timed mode

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP ,PPPoE, NTP, SMTP, UDP
ONVIF	Support ONVIF 2.4(Profile S/T/G)
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160 @20fps
Main Stream 2	2592*1536@20fps 2560*1440@30fps
Main Stream 3	1920*1080@20fps 1280*720@20fps

U-Link

8 MP IP Bullet camera , Fixed Lens

UL-8BIR20F-IP



Sub Stream 1	1280*720@20fps
Sub Stream 2	720*480@20fps
Tri Stream	1280*720@20fps 720*480@20fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(-Flicker Control), Video Tampering, HLC, Distortion
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	WDR: 120dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
Interface	
Audio	Optional 1 Built-in MIC
SD Card Slot	Optional Internal, Support Max 512GB
General	
Housing	Metal , IP67
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	171(W) × 73(H) × 70(D)mm
Weight	750g