

U-Link

8 MP AHD Bullet camera , VF Lens
UL-8BIR40V-AHD



FEATURES

1/2.5" CMOS sensor

Varifocal lens 2.8-12mm

Infrared Distance 40m

IP67 Metal Housing

U-Link

8 MP AHD Bullet camera , VF Lens UL-8BIR40V-AHD



SPECIFICATION

| SPECIFICATION | |
|------------------------|--|
| Camera | |
| Image Sensor | 1/2.5" CMOS sensor |
| Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimum Illumination | 0.01Lux |
| Scanning System | Progressive Scan |
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps |
| Night Vision | |
| IR Cut Filter | YES |
| Infrared LED | 42 x 4PCS |
| Infrared Distance | 40m |
| IR Status | AGC Auto Control |
| LENS | |
| Focus Length | 2.8-12mm |
| Focus Control | Manual |
| Lens Type | Varifocal |
| Camera Features | |
| Day/Night | YES/NO |
| OSD Menu | yes |
| WDR | DWDR |
| UTC | yes |
| Noise Reduction | DNR |
| Coaxial Audio | YES(only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |
| General | |
| Housing | Metal, IP67 |
| Bracket | YES |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 750mA |
| Dimension | 211(W) x 92(H) x 90(D)mm |
| Weight | 1400g |