

U-Link

8MP Outdoor Bullet IP Camera
with 3X motorized Zoom - IR 60m

UL-8BIR60VM-IP



FEATURES

1/1.8" OV High-resolution CMOS Sensor

H.264/H.265 Compression Method

3.6-11mm 3X Motor Zoom Auto Focus Lens

IR Distance 60m Max

IP 67 Outdoor Metal case

U-Link

8MP Outdoor Bullet IP Camera
with 3X motorized Zoom - IR 60m

UL-8BIR60VM-IP



SPECIFICATION

Camera	
Image Sensor	1/1.8" OV High-resolution CMOS Sensor
Resolution	8MP
Effective Pixels	3840(H)*2160(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset button	Optional
Lens	
Focus Length	3.6-11mm
Focus Control	Auto
Lens Type	Motorized
Pixels	8MP
Night Vision	
Infrared LED	42μ x 6PCS
Infrared Distance	60m
IR Status	Auto Control
IR Power On	Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4(Profile S/T)
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	3840*2160 @20fps 3072*2048@30fps
Main Stream 2	2592*1944@30fps 2560*1920@30fps
Main Stream 3	2560*1440@30fps 1920*1080@30fps 1280*720@30fps

U-Link

8MP Outdoor Bullet IP Camera
with 3X motorized Zoom - IR 60m

UL-8BIR60VM-IP



Sub Stream 1	720*480@20fps 720*480@30fps
Tri Stream	352*288@20fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(-Flicker Control), Video Tampering, HLC
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	WDR: 96dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Interface	
Audio	2-Way Audio
Alarm	1channel Input/Output
SD Card Slot	Optional, Support Max 512GB
General	
Housing	Metal , IP67
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 1100mA
Dimension	179(W) x 90(H) x 90(D)mm
Weight	1.65Kgs