

U-Link

8MP AHD Dome camera UL-8DIR25F-AHD



FEATURES

AHD/TVI HD Dome

1/2.5" CMOS sensor

3.6mm Fixed Lens

IR Distance Max. 25m



8MP AHD Dome camera

UL-8DIR25F-AHD



SPECIFICATION

Camera

| | |
|----------------------|--|
| Image Sensor | 1/2.5" CMOS sensor |
| Resolution | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080 |
| TV System | PAL/NTSC |
| Electronic Shutter | Auto |
| Minimum Illumination | 0.01Lux |
| Scanning System | Progressive Scan |
| Video Output Mode | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M@30fps/25fps/15fps, 2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps |

Night Vision

| | |
|-------------------|------------------|
| IR Cut Filter | YES |
| Infrared LED | 42μ x 2PCS |
| Infrared Distance | 25m |
| IR Status | AGC Auto Control |

LENS

| | |
|---------------|-------|
| Focus Length | 3.6mm |
| Focus Control | Fixed |
| Lens Type | Fixed |

Camera Features

| | |
|-----------------|-----------------|
| Day/Night | Yes/no |
| OSD Menu | yes |
| WDR | DWDR |
| UTC | yes |
| Noise Reduction | DNR |
| Coaxial Audio | YES (only TVI) |
| White Balance | AUTO / MANUAL |
| Gain Control | AUTO |

General

| | |
|-----------------------|-------------------------|
| Housing | Metal, IP67 |
| Bracket | No |
| Operation Temperature | -10°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 500mA |
| Dimension | ∅ 109 x 93(H) mm |
| Weight | 800g |