

U-Link

8ch XVR Support 1 SATA Port

UL-8XVRE



FEATURES

Support XVI/AHD/TVI/CVI/CVBS/IP

Support up to HD 5MP and IP 5MP Resolution recording

Support VGA, HDMI full HD output simultaneously

Support CVBS output

Support Max 8CH HD or 16CH IP Camera Input.

1*SATA ports Max 14TB



8ch XVR Support 1 SATA Port

UL-8XVRE



| Specifications | |
|------------------------------|---|
| System | |
| Main processor | NT98321 |
| Interface | |
| Operating interface | support 16-bit true color graphical menu interface and mouse operation |
| Preview | 1/4/8/9 |
| Video | |
| Codec | H.265+ |
| Preview ability | 8*1080N (6 in 1)/4*5M-N (6 in 1) |
| Encode ability | 8*1080N@15 fps(6 in 1)/4*5M-N@20fps(6 in 1) |
| Decode ability | 8*1080N@15 fps(6 in 1)/4*5M-N@20fps(6 in 1) |
| Multi-mode input | AHD:8*1080N;4*5M-N IP:16*1080P;8*5M |
| Motion Detection | Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel) |
| Audio | |
| Audio compression | G.711A |
| Intercom | support |
| Record & playback | |
| Record mode | manual>alarm>motion detection>timing |
| Local Playback | 4ch(analog input mode) |
| Search mode | Search by time, calendar, event, channel |
| Storage & backup | |
| Video storage | HDD, network |
| Backup mode | Network, USB hard disk, USB burner, SATA burner |
| External Interface | |
| Video input | 8ch BNC |
| Video output | 1ch VGA,1ch HDMI |
| Audio input | 1ch |
| Audio output | 1ch |
| Network interface | RJ45 10M/100M |
| PTZ control | Support kinds of PTZ protocols |
| USB | 2* USB 2.0 ports |
| HDD | 1*SATA ports (Max 14TB) |
| Wireless | 3G, WIFI (extend via USB) |



8ch XVR Support 1 SATA Port

UL-8XVRE



| General | |
|---------------------|---|
| Power supply | 12V/2A |
| Power Consumption | <15W (without HDD) |
| Working environment | Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa |
| Weight | 1.5KG |