

# U-Link

Wall Mounted LCD Monitor

## UL-M4301-LCD



### FEATURES

43" TFT-LCD.

Display color 16.7M.

Response time 8ms.

Life(hrs) >60,000(hrs).

Metal case SPCC.



Wall Mounted LCD Monitor

# UL-M4301-LCD



## SPECIFICATION

Model		UL-M4301-LCD
Panel size		43" TFT-LCD
Display area(mm)/mode		940(W)x529(H)/16:9
Maximum resolution		1680x1050
Display color		16.7M
Brightness (nits)		350cd/m <sup>2</sup>
Contrast		1200:1
Visual angle		178°/178°
Response time		8ms
Life(hrs)		>60,000(hrs)
Input and output (Mainboard interface)		
HDMI input		x2
DVI input		x1
VGA input		x1
USB		x1
BNC input		x3
BNC output		x3
AV input		x2
Power		
Power supply		AC100 ~ 240V 50/60 HZ
Maximum power consumption		<= 35W
Standby power consumption		<5W
Temperature		
Working temperature		0°C ~ 50°C
Storage Temperature		-20°C ~ 60°C
Working humidity		10% ~ 90%
Storage humidity		20% ~ 85%
Appearance		
Color/appearance		White, black, customized
Case		Metal case SPCC
Installation		Wall mount