

U-Link

4MP Pro IP Dome Camera

UL-4DIR40V-IP



FEATURES

1/2.8" SONY Starvis Back-illuminated CMOS Sensor

H.265+/H.265/H.264+/H.264 Compression Method

2.7-13.5mm Motorized Lens

IR Distance 40m Max.

With Internal POE and External SD Card Slot

U-Link

4MP Pro IP Dome Camera UL-4DIR40V-IP



SPECIFICATION

Camera

Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	4MP
Effective Pixels	2592 (H) x 1944 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec
Minimum Illumination	0.01Lux
S/N Ratio	>52dB
Scanning System	Progressive
Video Output	Network

Lens

Focus Length	2.7-13.5mm motor zoom
Focus Control	Auto
Lens Type	Auto
Pixel	4MP

Night Vision

Infrared LED	42μ x 4PCS
Infrared Distance	40m
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,PPPoE,NTP,STMP,UDB,SNMP
ONVIF	Support ONVIF 19.12(Profile S/T/G)
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Main Stream 3	1920*1080@30fps 1280*720@30fps
Main Stream 1	2592*1944@30fp
Main Stream 2	2560*1440@30fp

U-Link

4MP Pro IP Dome Camera UL-4DIR40V-IP



Sub Stream 1	1280*720@30fps 720*480@30fps
Sub Stream 2	352*288@30fps
Tri Stream	1280*720@30fps 720*480@30fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox , Mac Safari
Smart Phone	iPhone,Ipad, Android, Andriod pad
AI Function	
Intelligent Analysis	Face Detection, Intrusion Detetion, Line Cross Detetion, Loiter Detetion, People Gather Detecion, motion detection based on human detection
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	(Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion)
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	HDR : 120dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
Interface	
Audio	Optional Audio IN/OUT
Alarm	Optional 1 Channel Input/Ouput
SD Card Slot	Optional External, Support Max 512GB, Built in 4G Storage
General	
Housing	Metal , IP67
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C~+60°C RH95% Max
Power Source	DC12V+10%, 950mA
Dimension	ø140 x123(H)mm
Weight	1.2KG